

MATERIAL SAFETY DATA SHEET

Date of Issue: September 2001

Revised: February 2010

LEAD ACID BATTERY, WET**COMPANY DETAILS**

Company: Century Yuasa Batteries Pty. Ltd. (A.C.N. 009685232)
 Address: 49-65 Cobalt Street, Carole Park, QLD 4300 Australia
 Telephone Number: (07) 3361 6161 Fax Number: (07) 3361 6166
 Emergency Number: (07) 3361 6161

Hazardous according to criteria of Worksafe Australia.

IDENTIFICATION

Product Name: **LEAD ACID BATTERY, WET**
 Other Name: Battery, Wet, Filled with Acid, Electric Storage
 Manufacturers Product Code: Battery, Automotive
 UN Number: 2794
 Dangerous Goods Class: 8
 Packing Group: III
 Hazchem Code: 2W
 Poisons Schedule Number: S6
 Use: Starting, lighting, ignition for car, truck, etc

Physical Description/Properties

Appearance: The battery is a manufactured article. The sulphuric acid electrolyte is a clear, mobile liquid.
 (Sulphuric Acid Electrolyte)
 Boiling Point/Melting Point: (Sulphuric Acid Electrolyte) 95°C / -7 to -70°C
 Vapour Pressure: (Sulphuric Acid Electrolyte) 13 to 22 mmHg @ 25°C
 Specific Gravity: (Sulphuric Acid Electrolyte) 1.2 to 1.3 @ 25°C
 Flashpoint: (Sulphuric Acid Electrolyte) Not Applicable
 Flammability Limits: (Sulphuric Acid Electrolyte) Not Applicable
 Solubility in Water: (Sulphuric Acid Electrolyte) 100%

Other Properties

Sulphuric Acid: Contact with combustibles and organic materials may cause fire and explosion. Also reacts violently with strong reducing agents, metals, sulphur trioxide gas, strong oxidisers and water. Contact with metals may produce toxic sulphur dioxide fumes and may release flammable hydrogen gas.
 Lead Compounds: Avoid contact with strong acids, bases, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen and reducing agents.

Ingredients

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion by Weight</u>
Lead	7439-92-1	30 – 60%
Sulphuric Acid	7664-93-9	20 – 40%
Lead Dioxide	1309-60-0	10 – 30%

HEALTH HAZARD INFORMATION**Health Effects****Acute:**

Swallowed: Sulphuric acid - Corrosive and causes severe burns. May cause severe irritation of mouth, throat, oesophagus and stomach.
 Lead compounds - Acute ingestion may cause abdominal pain, nausea, vomiting, diarrhoea and severe cramping.
 Eye: Sulphuric acid - Severe irritation, burns, cornea damage, blindness.
 Lead compounds - May cause eye irritation.
 Skin: Sulphuric acid - Severe irritation, burns and ulceration.
 Lead compounds - Not readily absorbed through the skin.
 Inhaled: Sulphuric acid - Breathing of vapours or mists may cause respiratory irritation.
 Lead compounds - Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs.

Chronic:

Sulphuric acid: Possible erosion of tooth enamel, inflammation of nose, throat and bronchial tubes. Evidence available indicates exposure to strong inorganic acid mists containing sulphuric acid is carcinogenic to humans. (World Health Organisation: IARC. Copy draft report "Acid Toxicology" File, Chem. Prods NW Registry.) This classification does not apply to sulphuric acid solutions or to electrolyte in batteries.

Lead compounds: May cause constipation, weight loss, anaemia, fatigue, kidney damage, pain in joints, neuropathy (particularly of the motor nerves) and reproductive changes in male and female.

First Aid:

Swallowed: Sulphuric acid – Do not induce vomiting. Give a glass of water. Seek immediate medical assistance.

Eye Contact: Sulphuric acid – Irrigate with water for 15 minutes. Seek immediate medical assistance.

Skin Contact: Remove contaminated clothing and wash skin thoroughly with water. Seek medical assistance if symptoms persist.

Inhaled: Sulphuric acid – Apply artificial resuscitation and seek immediate medical assistance if not breathing.

Lead compounds – Gargle, wash nose and lips, seek immediate medical assistance.

First Aid Facilities: Access to a sufficient supply of potable water may be necessary.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Standard: Workplace Exposure Standard for Metallic Lead is 0.15 mg/m³ in air.
Workplace Exposure Standard for Sulphuric acid is 1 mg/m³ in air.

Engineering Controls: Use only in a well ventilated area.

Work Practices: Batteries are heavy, appropriate material handling equipment and techniques should be used. Handle batteries cautiously to avoid spills. Ensure vent caps are on securely. Avoid contact with internal components. Wear protective clothing when filling batteries as detailed below in "Personal Protection". Follow manufactures instructions for installation and service.

Personal Protection:

Respirator Type -	Not applicable under normal use.
Glove Type -	When handling Sulphuric acid, wear impervious PVC acid resistant gloves with elbow length gauntlet. When handling lead, wear leather or similar type work gloves.
Eye Protection -	When handling Sulphuric acid, wear chemical goggles/face shield.
Clothing -	When handling batteries, wear safety boots.

Flammability: Under some operating conditions or Sulphuric acid contact with most common metals, flammable hydrogen gas can be liberated, it is recommended that 2% hydrogen concentration is not exceeded. Do not use close to ignition sources. Use in a well ventilated area.

SAFE HANDLING INFORMATION

Storage and Transport: This product contains a Scheduled Poison (S6) and must therefore be stored, maintained and used in accordance with the relevant State Poisons Act. At all times store away from explosives, "dangerous when wet" substances, foodstuffs, oxidisable materials, organic peroxides, radioactive substances, combustible materials and sources of ignition. Check regularly for spills and leaks. Store batteries in cool, dry, well ventilated areas with adequate containment in the event of spills. The Australian Dangerous Goods Code defines battery transport requirements in Australia.

Spills: Wear personal safety equipment at all times as detailed in "Personal protection". Establish a hazard zone. Bund and neutralise liquid with Soda Ash or Sodium Bicarbonate. Slowly pour neutralising powder from the outside of the spill inwards. Continue until the entire spill is covered. Wait until the reaction is complete. Absorb excess liquid with dry earth, sand or a similar material.

Disposal: Refer to the local waste disposal authority for disposal of lead compounds, sulphuric acid and spent soda ash/sodium bicarbonate. Spent batteries should be sent to a secondary lead smelter for recycling.

Fire/Explosion Hazard**Fire Fighting Recommendations:**

Use Carbon Dioxide or Dry Chemical extinguishers. Firefighters to wear acid-resistant full protective clothing, including rubber footwear and self-contained breathing apparatus. Water (fine spray or fog) should not be used unless from a safe distance due to vigorous and exothermic reaction which will result.

List of Dangerous Decomposition or Combustion Products:

Sulphuric acid may decompose to sulphur trioxide, carbon monoxide, sulphuric acid mist, sulphur dioxide and hydrogen. Exposure of lead compounds to high temperatures are likely to produce toxic metal fume, contact with strong acid or base or presence of nascent hydrogen may generate highly toxic arsine gas. Exposure of plastic container and components to high temperatures may produce carbon dioxide, carbon monoxide, noxious aldehydes (eg. formaldehyde and acrolein), ketones, methane and ethane.

Safety Phrases:

S1/2: Keep locked up and out of reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S30: Never add water to this product.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible).

S53: Avoid exposure – obtain special instructions before use.

Risk Phrases:

R20/22: Harmful by inhalation and if swallowed.

R33: Danger of cumulative effects.

R35: Causes severe burns.

R58: May cause long term adverse effects in the environment.

R61: May cause harm to the unborn child.

R62: Possible risk of impaired fertility.

CONTACT POINT

Technical Manager: (07) 3361 6161

Company Disclaimer:

This Material Safety Data Sheet is offered solely for information, consideration and investigation to determine the suitability of adopting safety and health precautions as may be necessary under the user's specific conditions and processes. All such conditions and processes are beyond the control of Century Yuasa Batteries Pty. Ltd.

The information contained herein was obtained from selected publications which Century Yuasa Batteries Pty. Ltd. believes to be reliable. However, Century Yuasa Batteries Pty. Ltd. provides no warranties, either expressed or implied, and assumes no responsibility for the accuracy or completeness of this information.

Century Yuasa Batteries Pty. Ltd. reserves the right to revise this Material Safety Data Sheet as information becomes available. The user has the responsibility, by making contact with this company or otherwise, to make certain the Material Safety Data sheet being consulted is the latest issued.