

SPECIFICATIONS

Model	RTV-X1140 Work Site	
Body color	Kubota Orange	
Make	KUBOTA D1105-E4-UV-2	
Type	3-cylinders, 4-cycle, diesel, OHV	
Displacement	cc	1123
Horsepower*	HP (kW)/rpm	24.8 (18.5)/3000
Cooling system	Liquid-cooled	
Fuel tank capacity	ℓ	30
Transmission	Variable hydro transmission (VHT-X)	
Max. Travelling speed	mph (km/h)	25 (40)
Wheels, drive system	4WD	
Front differential lock	Limited-slip differential	
Rear differential lock	Foot operated differential lock	
Gear selection	Hi-Lo range forward, Neutral, Reverse	
Brakes	Front / Rear	Wet-disc brake
Parking brake	Rear wheel, hand operated	
Steering	Hydrostatic power steering	
Suspension	Dual A-Arms independent suspension	
Length	mm	3610
Width	mm	1605
Height, overall	mm	2025
Front tread centers	mm	1280 (HDWS)
Rear tread centers	mm	1280 (HDWS)
Wheelbase	mm	2495
Ground clearance	Front axle / Rear axle	285 / 240
Turning radius	m	5.2
Towing capacity	kg	590
Payload capacity	kg	739
Curb weight	kg	1075
Width	mm	1465
Length	Long / Short	1300 / 660
Depth	mm	285
Volume	Long / Short	0.54 / 0.28
Bed height (no load)	mm	900
Load capacity	Long / Short	500 / 300
Front	25×10×12 HDWS, 6-PLY	
Rear	25×10×12 HDWS, 6-PLY	
Wheels	Front / Rear	Steel
Hydraulic bed lift	Standard on both short / long bed mode	

* SAE J1995
 The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only. Photograph taken on closed driveway for demonstrative purposes only.